

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 231 363 A2**

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
14.08.2002 Bulletin 2002/33

(51) Int Cl.7: **F01N 3/022**

(21) Application number: **02002759.5**

(22) Date of filing: **07.02.2002**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Ishihara, Mikio
Kariya-city, Aichi-pref. 448-8661 (JP)
• Nishimura, Mamoru
Kariya-city, Aichi-pref. 448-8661 (JP)

(30) Priority: **09.02.2001 JP 2001034177**
07.08.2001 JP 2001239685


(74) Representative:
Leson, Thomas Johannes Alois, Dipl.-Ing.
Patentanwälte
Tiedtke-Bühling-Kinne & Partner,
Bavariaring 4
80336 München (DE)

(71) Applicant: **Denso Corporation**
Kariya-city, Aichi-pref., 448-8661 (JP)

(54) **Honeycomb particulate filter structure constituted by main and sub honeycomb structures**

(57) A honeycomb structure comprising at least one main honeycomb structure 10 and sub-honeycomb structures 21, 22 axially disposed, in series, on both end surfaces of the main honeycomb structure 10. Partial plugs 15 are constituted for some of the cells 11 of the main honeycomb structure 10 by facing the intersecting

portions of partitioning walls 211, surrounding the cells of the sub-honeycomb structure 21 disposed adjacent to the main honeycomb structure with some of the cells of main honeycomb structure, and the arrangement of the partial plugs 15 at one end surface 101 of the main honeycomb structure differs from that at the other end surface of the main honeycomb structure 10.



EP 1 231 363 A2

Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to a honeycomb structure used for a filter for purifying an exhaust gas or the like.

2. Description of the Related Art

[0002] As means for removing particulate matters such as fine carbon particles and like particles emitted from an internal combustion engine such as of an automotive engine, there has been employed a method of once trapping particulate matters by using a honeycomb filter and removing the particulate matters by heating or burning them using a heater or a catalyst.

[0003] The conventional filter for purifying the exhaust gas employs a honeycomb structure in which, as shown in Figs. 12 and 13, one end of cells 90 of the ceramic honeycomb structure 9, with both ends, are alternately closed with plugs 95. That is, referring to Fig. 13, the end surfaces 91 on the upstream side are alternately plugged, checkerwise, for example, by plugs 95 at the end of the cell 90. The cells having plugs on the upstream side are left open on their downstream side, and the cells which are opened on their upstream side are closed with plugs on the downstream side. A catalyst is carried on the partitioning walls 98, depending upon the kind of the filter for purifying the exhaust gas.

[0004] The above filter for purifying the exhaust gas traps the particulate matters on the partitioning walls thereof when an exhaust gas from an internal combustion engine passes therethrough, and the particulate matters are removed by being heated and burned using a heater or based upon the catalytic action.

[0005] However, the above-mentioned conventional filter 9 for purifying the exhaust gas has problems, as described below.

[0006] That is, as shown in Fig. 14, particulate matters 88 trapped from the exhaust gas 8 flowing into the exhaust-gas purifying filter are not necessarily removed by burning in good timing, so that they are often deposited gradually on the partitioning walls 98. For example, while the exhaust gas 8 of a low temperature is being emitted from the internal combustion engine, the burning does not take place despite the catalytic action, and the particulate matters 88 are simply deposited. In this case, the pressure loss increases when the exhaust gas 8 passes through the filter, i.e., through the honeycomb structure, and the filter is abnormally heated and may become cracked or melt-damaged by the heat of burning.

[0007] Further, the process of plugging cells of the honeycomb structure at the ends thereof requires very cumbersome and laborious manual work, hindering ef-

forts to decrease the cost of production.

SUMMARY OF THE INVENTION

5 [0008] The present invention was accomplished in view of the problems inherent in the conventional art, and provides a honeycomb structure capable of suppressing the occurrence of excessive pressure loss caused by the deposition of particulate matters and of
10 being produced at a decreased cost.

[0009] According to one aspect of the present invention, there is provided a honeycomb structure comprising at least one main honeycomb structure and sub-honeycomb structures axially disposed, in series, on both
15 end surfaces of the main honeycomb structure, wherein partial plugs are constituted for some of the cells of the main honeycomb structure by facing the intersecting portions of partitioning walls, surrounding the cells of the sub-honeycomb structures disposed adjacent to the
20 main honeycomb structure, with some of the cells of the main honeycomb structure and the arrangements of the partial plugs at one end surface of the main honeycomb structure differs from that at the other end surface of the main honeycomb structure.

25 [0010] The actions and effects of the invention will now be described.

[0011] As described above, the honeycomb structure of the present invention is constituted by combining the main honeycomb structure and the sub-honeycomb
30 structures. The sub-honeycomb structures work as partial plugs for partially closing some cells of the main honeycomb structure. The partial plugs at the left end surface of the main honeycomb structure are arranged differently from those at the right end surface of the main
35 honeycomb structure.

[0012] Therefore, the honeycomb structure has a construction such that the openings on one end of the cells of the main honeycomb structure, between both ends thereof, are at least partially closed by the partial
40 plugs constituted by the sub-honeycomb structure. When the honeycomb structure is disposed in a fluid, therefore, as the fluid enters into the cells a difference occurs in the flow resistance of the fluid, depending upon the presence of the partial plugs, in the upstream end
45 surface of the main honeycomb structure. Accordingly, the fluid easily enters into the cells without the partial plugs at the upstream end surface thereof.

[0013] In the cells having the partial plugs on the downstream end surface of the main honeycomb structure, a condition is established wherein a fluid encounters a smaller resistance, when it flows through a partitioning wall into a cell without a partial plug on the downstream side, than when it flows to the downstream side through the partial plugs on the downstream end surface
50 of the main honeycomb structure. When the honeycomb structure is used, for example, for a filter for purifying an exhaust gas, the exhaust gas, which is the fluid, flows through the partitioning walls at a larger flow rate than

when it flows through the main honeycomb structure without plugs, so that it is possible to trap the particulate matters in the exhaust gas by the partitioning walls with improved efficiency.

[0014] The plugs constituted by the sub-honeycomb structure are partial plugs which do not fully close the cells of the main honeycomb structure but only partially close them. This suppresses the problem, as explained above, that occurs when the cells are completely closed by the conventional plugs.

[0015] That is, when the cells are completely plugged, only a little of the fluid flows through the partitioning walls under an abnormal condition where the particulate matters have been excessively deposited on the partitioning walls, and the pressure in the cells rises excessively. According to the present invention, on the other hand, the cells of the main honeycomb structure are partially plugged, so that even in an abnormal condition where the pressure has been raised in the cells, the fluid flows through a space in a cell left by the partial plugs, and the pressure is not excessively elevated.

[0016] Further, the sub-honeycomb structure has the intersecting portions of the partitioning walls facing the cells of the main honeycomb structure to form the partial plugs. Therefore, no cumbersome production process needs to be executed, unlike the conventional plugging process. This makes it possible to produce the honeycomb structure at a decreased cost and more efficiently.

[0017] According to the present invention, therefore, it is possible to suppress the occurrence of excessive pressure loss caused by the deposition of particulate matters and to provide a honeycomb structure at a decreased cost.

[0018] According to another aspect of the present invention, it is preferable that the ratio of the total length of the sub-honeycomb structures in the axial direction thereof to the length of the whole honeycomb structure in the axial direction thereof, be in a range of from 5 to 60%. When the above ratio is less than 5%, the honeycomb structure has a decreased strength and may become cracked. When the ratio exceeds 60%, on the other hand, the main honeycomb structure possesses a decreased filtering area, so that it has considerably decreased capacity to trap the particulate matters.

[0019] According to a further aspect of the present invention, preferably, both the cells of the main honeycomb structure and the cells of the sub-honeycomb structures located at the ends of the main honeycomb structure, have a square shape and are arranged with their sides being inclined by about 45 degrees relative to each other and intersecting. In this case, the intersecting portions of partitioning walls of the sub-honeycomb structures can be regularly arranged relative to the cells of the main honeycomb structure, and hence the partial plugs can be regularly arranged. Therefore, an enhanced effect is obtained by the arrangement of the partial plugs.

[0020] According to a still further aspect of the present

invention, it is preferable that the main honeycomb structure and the sub-honeycomb structures be joined together with an adhesive. In this case, the main honeycomb structure and the sub-honeycomb structures can be firmly secured together and deviation in the positional relationship between them can be prevented during the use.

[0021] According to a yet further aspect of the present invention, a casing is arranged to surround the honeycomb structure, and the arrangement of the main honeycomb structure and of the sub-honeycomb structures is secured by the casing. In this case, it is possible to omit the step of adhering the main honeycomb structure and the sub-honeycomb structures together, and thus to simplify the production process.

[0022] According to a still further aspect of the present invention, it is preferable that the main honeycomb structure be made of a ceramic material. As the main honeycomb structure, the partitioning walls thereof can be made of a metal or any other material as long as they can have permeability. Among them, a ceramic material is preferable, because it can easily realize the honeycomb structure having partitioning walls, with pores, exhibiting permeability.

[0023] The sub-honeycomb structures may be made of a ceramic material, a metal, etc.

[0024] According to another aspect of the present invention, it is preferable that the intersecting portions of partitioning walls of the sub-honeycomb structure have an increased thickness. In this case, the partial plugs exhibit an enhanced effect.

[0025] According to a further aspect of the present invention, there is provided a honeycomb structure in which a plurality of honeycomb structures are arranged in series, and partitioning walls of a first honeycomb structure are disposed so as to face at least some of the cells in a second honeycomb structure, and when a fluid flows in the direction in which the plurality of honeycomb structures are arranged in series, the flow resistance of the fluid in a passage formed by a cell defined by the partitioning walls in the second honeycomb structure located on the upstream side of the first honeycomb structure varies from a next passage formed by the adjacent cell, though all cells of the second honeycomb structure.

[0026] In the honeycomb structure of the present invention, each flow resistance of the fluid flowing through the cells in the honeycomb structure located on the upstream side is set to differ between two adjacent cells by the above-mentioned combination of the plurality of the honeycomb structures. Hence, a fluid entering into cells having high flow resistances flows through the partitioning walls into adjacent cells having low flow resistances. Therefore, a notable advantage is obtained when the above-mentioned honeycomb structure is used for the filter.

[0027] According to a further aspect of the present invention, there is provided a honeycomb structure in which a plurality of honeycomb structures are arranged

in series, and partitioning walls of the first honeycomb structure are disposed so as to face at least some of the cells in the second honeycomb structure, and when a fluid flows in a direction in which the plurality of honeycomb structures are arranged in series, the density of cells of the second honeycomb structure located on the upstream side is higher than the density of cells of the first honeycomb structure located on the downstream side.

[0028] In the honeycomb structure of the present invention as described above, the density of cells in the honeycomb structure on the upstream side is higher than that of the honeycomb structure of the downstream side. Accordingly, the open surfaces of the cells of the honeycomb structure on the upstream side, which include the portions facing the partitioning walls of the honeycomb structure on the downstream side and the open portions, can be easily formed. It is therefore possible to set the flow resistance of the fluid flowing through a cell in the honeycomb structure located on the upstream side so as to differ from the adjacent cell thereof. Hence, the fluid entering into a cell having high flow resistance flows through the partitioning walls into the adjacent cells having low flow resistances. Therefore, a notable advantage is obtained when the above-mentioned honeycomb structure is used for the filter.

[0029] According to a further aspect of the present invention, the above-mentioned plurality of honeycomb structures can be arranged with a gap, which is not larger than 10 mm, between two adjacent honeycomb structures. When the gap exceeds 10 mm, the effect of adjusting the flow resistances between the adjacent cells on the upstream side is not achieved to a sufficient degree despite arranging the plurality of honeycomb structures in series.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030]

Fig. 1 is a perspective view of a honeycomb structure according to an embodiment 1;
 Fig. 2 is a diagram illustrating an end surface of the honeycomb structure according to embodiment 1 as viewed from the direction of an arrow A in Fig. 1;
 Fig. 3 is a diagram illustrating an end surface of the honeycomb structure according to embodiment 1 as viewed from the direction of an arrow B in Fig. 1;
 Fig. 4 is a view illustrating a filter for purifying the exhaust gas according to embodiment 1;
 Fig. 5 is a perspective view of the honeycomb structure according to an embodiment 2;
 Fig. 6 is a perspective view of the honeycomb structure according to an embodiment 3;
 Fig. 7 is a diagram illustrating an end surface of the honeycomb structure according to embodiment 3 as viewed from the direction of an arrow A in Fig. 6;
 Fig. 8 is a diagram illustrating an end surface of the

honeycomb structure according to embodiment 3 as viewed from the direction of an arrow B in Fig. 6;
 Fig. 9 is a diagram illustrating the flow resistance of a fluid according to embodiment 3;

Fig. 10 is a diagram illustrating an end surface of the honeycomb structure according to an embodiment 4 as viewed from a direction corresponding to the direction of the arrow A in Fig. 1;

Fig. 11 is a diagram illustrating an end surface of the honeycomb structure according to embodiment 4 as viewed from a direction corresponding to the direction of the arrow B in Fig. 1;

Fig. 12 is a diagram illustrating an end surface of the honeycomb structure according to a prior art;

Fig. 13 is a diagram illustrating in longitudinal cross section the honeycomb structure according to the prior art; and

Fig. 14 is a diagram, illustrating a problem that occurs when the particulate matters deposit on the partitioning walls, in the prior art.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiment 1.

[0031] The honeycomb structure according to an embodiment of the present invention will now be described with reference to Figs. 1 to 4.

[0032] Referring to Fig. 1, the honeycomb structure 1 of this embodiment includes a main honeycomb structure 10, and two sub-honeycomb structures 21 and 22 axially arranged in series on both end surfaces of the main honeycomb structure 10.

[0033] Referring to Figs. 2 and 3, intersecting portions of partitioning walls 211, 221, surrounding the cells of the sub-honeycomb structures 21, 22 disposed adjacent to the main honeycomb structure 10, face some of the cells 11 of the main honeycomb structure 10 so as to constitute partial plugs 15. Here, the arrangement of the partial plugs 15 differs between the one end surface 101 and the other end surface 102 of the main honeycomb structure 10.

[0034] This will now be described in detail.

[0035] In this embodiment, the main honeycomb structure 10 and the sub-honeycomb structures 21, 22 have partitioning walls 111, 211, 221 in the shape of a square lattice as shown in Figs. 2 and 3, and have many square cells. The honeycomb structures 10, 21, 22 are all made of a ceramic material chiefly comprising a cordierite. At least the partitioning walls 111 have a number of pores to maintain gas permeability.

[0036] The main honeycomb structure 10 and the sub-honeycomb structures 21, 22 all have outer sizes of 129 mm diameter. Further, the main honeycomb structure 10 has a length of 130 mm while the sub-honeycomb structures 21, 22 have a length of 10 mm, respectively, and the ratio of the total length of the sub-

honeycomb structures 21, 22 in the axial direction thereof to the length of the whole honeycomb structure 1 in the axial direction thereof is made to be 13%.

[0037] The main honeycomb structure 10 has a cell size such that the partitioning wall is 0.3 mm thick and the cell pitch, i.e., the side of the cell, is 0.74 mm, and the diagonal line is 1.05 mm long. The sub-honeycomb structures 21, 22 have cell sizes such that the partitioning walls are 0.3 mm thick and the cell pitches (lengths of the sides) are 1.47 mm, respectively. That is, the cell pitch (length of the side) of the sub-honeycomb structures 21, 22 is selected to be the same as the pitch in the direction of the diagonal line (length of a diagonal line) of the main honeycomb structure 10.

[0038] In the sub-honeycomb structures 21, 22, further, the respective intersecting portions of the partitioning walls 211, 221 are thickened so as to thicken the cell corner portions as shown in Figs. 2 and 3.

[0039] In this embodiment, further, the sub-honeycomb structures 21, 22 are joined to both axial end surfaces 101, 102 of the main honeycomb structure 10, respectively, by using an adhesive.

[0040] Here, as shown in Figs. 2 and 3, the partitioning walls 111 of the main honeycomb structure 10 and the respective partitioning walls 211, 221 of the sub-honeycomb structures 21, 22 are arranged so as to intersect, being inclined each other by about 45 degrees.

[0041] As shown in Figs. 2 and 3, further, the positions, on one end surface 101 of the main honeycomb structure 10, where the partial plugs 15 formed by the intersection of the partitioning walls 211 of the sub-honeycomb structure 21 are present, are different from the positions, on the other end surface 102 of the main honeycomb structure 10, where the partial plugs 15 formed by the intersection of the partitioning walls 221 of the sub-honeycomb structure 22 are situated, which means that the former positions are alternately arranged against the latter positions when both of the positions are in the same plane.

[0042] That is, the cells 11a having the partial plugs 15 on the one end surface 101 of the cell 11a as shown in Fig. 2 are opened, without the partial plugs 15, on the other end surface 102 thereof as shown in Fig. 3. On the other hand, the open cells 11b without the partial plugs 15, on one end surface 101 of the cells 11b as shown in Fig. 2 are provided with the partial cells 15 on the other end surface 102 thereof, as also shown in Fig. 3.

[0043] In this embodiment, the cells 11b of the main honeycomb structure 10 are closed by the partial plugs 15 at a ratio of about 85% in terms of the area.

[0044] In this embodiment, the thus constituted honeycomb structure 1 is used as a carrier to constitute a filter for purifying the exhaust gas. Concretely speaking, as shown in Fig. 4, a catalyst is carried by the honeycomb structure 1 which is accommodated in a casing 5.

[0045] The following actions are exhibited when the filter employing the honeycomb structure 1 for purifying

the exhaust gas is disposed in the exhaust gas passage.

[0046] That is, the exhaust gas colliding with one end surface 101 on the upstream side tends to selectively enter into the cells 11b (Fig. 2) without the partial plugs 15 due to the resistance produced by the partial plugs 15.

[0047] Further, the cells 11b have the partial plugs 15 on the downstream side as shown in Fig. 3, which creates a circumstance in that the fluid encounters lower resistance when it flows into the cells 11a without the partial plugs 15 on the downstream side through the partitioning walls 111 so as to flow out the cells 11a rather than when it flows to the downstream side through the partial plugs 15 on the downstream end surfaces of the cells 11b.

[0048] Therefore, when the above-mentioned honeycomb structure 1 is used as a carrier of the filter for purifying the exhaust gas, the exhaust gas, which is the fluid, passes through the partitioning walls 111 at an increased flow rate as compared to when only the main honeycomb structure 10 having no plug is used, so that the particulate matters contained in the exhaust gas can be trapped with improved efficiency.

[0049] The plugs constituted by the sub-honeycomb structures 21, 22 do not completely close the cells of the main honeycomb structure but are the partial plugs 15 for partially closing them. Under an abnormal condition where the particulate matters have been excessively deposited on the partitioning walls 111, the fluid passes through spaces in cells left by the partial plugs 15, and the pressure is not excessively elevated.

[0050] The sub-honeycomb structures 21 and 22 form the partial plugs with their intersecting portions of the partitioning walls 211, 221 facing the cells 11 of the main honeycomb structure 10. This eliminates a cumbersome of production process such as plugging employed in the prior art. Accordingly, the honeycomb structure 1 is produced at low cost and efficiently.

[0051] As described above, this embodiment provides a honeycomb structure 1 which suppresses the occurrence of excessive pressure loss caused by the deposition of particulate matters, and which can be produced at a low cost.

[0052] In this embodiment, the main honeycomb structure 10 and the sub-honeycomb structures 21, 22 are joined together with an adhesive. They may, however, be secured together by using the above-mentioned casing without using an adhesive.

Embodiment 2.

[0053] In this embodiment as shown in Fig. 5, there are used a plurality of main honeycomb structures 31 to 33, and the main honeycomb structures 31 to 33 and the sub-honeycomb structures 41 to 44 are alternately arranged. The main honeycomb molded structures 31 to 33 are the same ceramic honeycomb structures as the main honeycomb structure 10 of the embodiment 1

with the exception of shortening the length thereof to 36 mm. The sub-honeycomb structures 41, 43 are the same as the sub-honeycomb structure 21 of the embodiment 1, and the sub-honeycomb structures 42, 44 are the same as the sub-honeycomb structure 22 of the embodiment 1. As shown in Fig. 5, they are arranged in series in the axial direction, and are adhered together with an adhesive. In other respects, this embodiment is the same as the embodiment 1.

[0054] In this case, the above-mentioned state of Fig. 2 and the state of Fig. 3 are alternately repeated due to the presence of the sub-honeycomb structures 41 to 44. When the honeycomb structure is used as a filter for purifying the exhaust gas in the same manner as in embodiment 1, therefore, the exhaust gas, which is the fluid, passes through the partitioning walls of the main honeycomb structures 31 to 33, i.e., passes through the partitioning walls three times. As a result, the particulate matters can be trapped with improved efficiency.

[0055] In other respects, the actions and effects are the same as those of the embodiment 1.

[0056] The above-mentioned embodiments have dealt with the cases where the main honeycomb structures and the sub-honeycomb structures possess square-shaped cells. However, as long as the above-mentioned partial plugs can be formed, the honeycomb structure may possess cells of any other shape, such as a triangular shape or a hexagonal shape.

Embodiment 3.

[0057] The honeycomb structure 6 of this embodiment includes three honeycomb structures 61, 62 and 63 that are arranged in series as shown in Fig. 6. The two adjacent honeycomb structures are arranged so that the partitioning walls of one honeycomb structure face the openings of at least some of the cells of the other honeycomb structure.

[0058] When the fluid flows in the direction in which the three honeycomb structures 61, 62 and 63 are arranged in series, the honeycomb structure 61 located on the upstream side has a higher density of cells than the density of cells of the honeycomb structure 62 located on the downstream side and the honeycomb structure 62 located on the upstream side has a higher density of cells than the density of cells of the honeycomb structure 63 located on the downstream side.

[0059] Concretely speaking, the honeycomb structure 61 on the most upstream side has a density of cells of 900 meshes, the honeycomb structure 62 at the center has a density of cells of 600 meshes, and the honeycomb structure 63 on the most downstream side has a density of cells of 300 meshes.

[0060] Fig. 7 illustrates a state where the honeycomb structure 6 is viewed from the front on the upstream side (from the direction of an arrow A in Fig. 6). Fig. 7 illustrates the partitioning walls 611 of the honeycomb structure 61 on the most upstream side, and the partitioning

walls 621 of the central honeycomb structure 62 located at the back thereof. The honeycomb structure 61 on the most upstream side has cells 610, which have closed cells 610b facing the partitioning walls of the central honeycomb structure 62 and open cells 610a, which are alternately arranged, in the open surface on the downstream side thereof.

[0061] Fig. 8 illustrates a state where the honeycomb structure 6 is viewed from the front on the downstream side (from the direction of an arrow B in Fig. 6). Fig. 8 illustrates the partitioning walls 631 of the honeycomb structure 63 on the most downstream side, and the partitioning walls 621 of the central honeycomb structure 62 located at the back thereof. The central honeycomb structure 62 has cells 620, which have closed cells 620b facing the partitioning walls 631 of the honeycomb structure 63 on the most downstream side and open cells 620a, which are alternately arranged, in the open surface on the downstream side thereof.

[0062] Fig. 9 schematically illustrates a positional relationship between the partitioning walls 611 of the honeycomb structure 61 on the most upstream side and the partitioning walls 621 of the central honeycomb structure 62. In the cells 610 in the honeycomb structure 61 in Fig. 9, the flow resistance of the open cell 610a without the partitioning wall 621 of the honeycomb structure 62 in the open surface on the downstream side thereof is denoted by P1, the flow resistance of the closed cell 610b having the partitioning wall 621 of the honeycomb structure 62 disposed in the open surface on the downstream side thereof is denoted by P2, and the resistance created as the fluid flows from the closed cell 610b into the open cell 610a through the partitioning wall 611 is denoted by P3. Here, in this embodiment, there holds a relationship $P1 < P3 < P2$.

[0063] This permits the fluid flowing through the closed cell 610b to efficiently flow into the open cell 610a through the partitioning wall 611, to easily obtain excellent filtering effect through the partitioning wall 611.

[0064] Such an action and effect are similarly obtained even between the central honeycomb structure 62 and the downstream honeycomb structure 63; i.e., the honeycomb structure 6 as a whole exhibits two steps of excellent filtering effect.

Embodiment 4.

[0065] In this embodiment as shown in Figs. 10 and 11, the shapes of the cells are changed in the main honeycomb structure 10 and in the two sub-honeycomb structures 21, 22, axially disposed, in series, on both ends of the main honeycomb structure 10, in the embodiment 1.

[0066] In this embodiment, the main honeycomb structure 10 as well as the sub-honeycomb structures 21, 22 have a triangular shape. As shown in Figs. 10 and 11, partial plugs 15 are formed for some of the cells 11 of the main honeycomb structure 10 by facing the

intersecting portions of the partitioning walls 211, 221, surrounding the cells of the sub-honeycomb structures 21, 22 adjacent to the main honeycomb structure 10, with the some of the cells 11 of the main honeycomb structure 10. Further, the arrangement of the partial plugs 15 at the one end surface 101 of the main honeycomb structure 10 differs from and the arrangement of the partial plugs 15 at the other end surface 102 of the main honeycomb structure 10.

[0067] In this embodiment, even the cells 11 without the partial plugs 15 face part of the partitioning walls 211, 221 of the sub-honeycomb structures 21, 22, which produces a flow resistance, to some extent, which, however, is sufficiently smaller than the flow resistance produced by the partial plugs 15 formed by the intersecting portions of the partitioning walls.

[0068] In other respects, this embodiment is the same as embodiment 1.

[0069] In this case, too, the same actions and effects are obtained as those of embodiment 1.

[0070] A honeycomb structure comprising at least one main honeycomb structure 10 and sub-honeycomb structures 21, 22 axially disposed, in series, on both end surfaces of the main honeycomb structure 10. Partial plugs 15 are constituted for some of the cells 11 of the main honeycomb structure 10 by facing the intersecting portions of partitioning walls 211, surrounding the cells of the sub-honeycomb structure 21 disposed adjacent to the main honeycomb structure with some of the cells of main honeycomb structure, and the arrangement of the partial plugs 15 at one end surface 101 of the main honeycomb structure differs from that at the other end surface of the main honeycomb structure 10

Claims

1. A honeycomb structure comprising;

at least one main honeycomb structure and sub-honeycomb structures axially disposed, in series, on both end surfaces of said main honeycomb structure;
wherein partial plugs are constituted for some of the cells of said main honeycomb structure by facing the intersecting portions of partitioning walls, surrounding the cells of said sub-honeycomb structures disposed adjacent to the main honeycomb structure with the some of the cells of main honeycomb structure, and the arrangement of said partial plugs at one end surface of the main honeycomb structure differs from that at the other end surface of said main honeycomb structure.

2. A honeycomb structure according to claim 1, wherein said main honeycomb structures are used in a plural number, and said main honeycomb struc-

tures and said sub-honeycomb structures are alternately arranged.

3. A honeycomb structure according to claim 1 or 2, wherein

the ratio of the total length of said sub-honeycomb structures in the axial direction thereof to the length of the whole honeycomb structure in the axial direction thereof, is in a range of from 5 to 60%.

4. A honeycomb structure according to any one of claims 1 to 3, wherein both the cells of said main honeycomb structure and the cells of said sub-honeycomb structures located at the ends of the main honeycomb structure have a square shape and are arranged with their sides being inclined by about 45 degrees relative to each other and being intersected.

5. A honeycomb structure according to any one of claims 1 to 4, wherein said main honeycomb structure and said sub-honeycomb structures are joined together with an adhesive.

6. A honeycomb structure according to any one of claims 1 to 5, wherein a casing is arranged to surround said honeycomb structure, and the arrangement of said main honeycomb structure and of said sub-honeycomb structures is secured by said casing.

7. A honeycomb structure according to any one of claims 1 to 6, wherein said main honeycomb structure is made of a ceramic material.

8. A honeycomb structure according to any one of claims 1 to 7, wherein the intersecting portions of partitioning walls of said sub-honeycomb structure have an increased thickness.

9. A honeycomb structure, in which a plurality of honeycomb structures are arranged in series, and partitioning walls of a first honeycomb structure are disposed so as to face at least some of the cells in a second honeycomb structure, and

when a fluid flows in a direction in which said plurality of honeycomb structures are arranged in series, the flow resistance of the fluid in a fluid passage formed by a cell defined by the partitioning walls in the second honeycomb structure located on the upstream side of the first honeycomb structure varies from a next passage formed by the adjacent cell, through all cells of the second honeycomb structure.

10. A honeycomb structure in which a plurality of honeycomb structures are arranged in series, and partitioning walls of a first honeycomb structure are disposed so as to face at least some of the cells in a second honeycomb structure, and when a fluid flows in a direction in which said plurality of honeycomb structures are arranged in series, the density of cells of the second honeycomb structure located on the upstream side is higher than the density of cells of the first honeycomb structure located on the downstream side.

11. A honeycomb structure according to claim 9 or 10, wherein

in the cells in the second honeycomb structure, when the flow resistance of the open cell without the partitioning wall of the first honeycomb structure in the open surface on the downstream side thereof is denoted by P1, the flow resistance of the closed cell having the partitioning wall of the first honeycomb structure disposed in the open surface on the downstream side thereof is denoted by P2, and the flow resistance created as the fluid flows from said closed cell into said open cell through the partitioning wall is denoted by P3, there exists a relationship $P1 < P3 < P2$.

12. A honeycomb structure according to any one of claims 9 to 11, wherein said plurality of honeycomb structures are arranged with a gap, which is not larger than 10 mm, between two adjacent honeycomb structures.

Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8




Fig.9




Fig.10




Fig.11




Fig.12




Fig.13





Fig.14



(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 231 363 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
09.06.2004 Bulletin 2004/24

(51) Int Cl.7: **F01N 3/022, F01N 3/031**

(43) Date of publication A2:
14.08.2002 Bulletin 2002/33

(21) Application number: **02002759.5**

(22) Date of filing: **07.02.2002**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Ishihara, Mikio**
Kariya-city, Aichi-pref. 448-8661 (JP)
• **Nishimura, Mamoru**
Kariya-city, Aichi-pref. 448-8661 (JP)

(30) Priority: **09.02.2001 JP 2001034177**
07.08.2001 JP 2001239685

(74) Representative:
Leson, Thomas Johannes Alois, Dipl.-Ing.
Patentanwälte
Tiedtke-Bühling-Kinne & Partner,
Bavariaring 4
80336 München (DE)

(71) Applicant: **Denso Corporation**
Kariya-city, Aichi-pref., 448-8661 (JP)

(54) Honeycomb particulate filter structure constituted by main and sub honeycomb structures

(57) A honeycomb structure for particulate filter comprising at least one main honeycomb structure (10) and sub-honeycomb structures (21,22) axially disposed, in series, on both end surfaces of the main honeycomb structure (10). Partial plugs (15) are constituted for some of the cells (11) of the main honeycomb structure (10) by facing the intersecting portions of partition-

ing walls (211), surrounding the cells of the sub-honeycomb structure (21) disposed adjacent to the main honeycomb structure with some of the cells of main honeycomb structure, and the arrangement of the partial plugs (15) at one end surface (101) of the main honeycomb structure differs from that at the other end surface of the main honeycomb structure (10).




Fig.1

EP 1 231 363 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 00 2759

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 153 157 A (HONDA MOTOR CO LTD) 28 August 1985 (1985-08-28) * page 2, line 33 - page 3, line 13; figures 1-3 *	9,12	F01N3/022 F01N3/031
A	DE 42 03 128 A (NISSAN MOTOR) 13 August 1992 (1992-08-13) * column 2, line 38 - column 4, line 1; figures 1-7 *	1,9,10	
A	US 4 464 185 A (TOMITA MASAHIRO ET AL) 7 August 1984 (1984-08-07) * column 2, line 42 - column 4, line 32; claim 1; figures 1,2 *	1,9,10	
A	US 6 013 599 A (MANSON IAN) 11 January 2000 (2000-01-11) * column 6, line 8 - line 11; figure 1 *	1,9,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			F01N
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 4 March 2004	Examiner Torle, E
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P/AC01)



European Patent
Office

Application Number

EP 02 00 2759

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☐ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☒ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

LACK OF UNITY OF INVENTION
SHEET B

Application Number

EP 02 00 2759

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-8

A honeycomb structure having a main honeycomb structure wherein some cells are partially closed by a upstream sub-honeycomb structure and some other cells are partially closed by a downstream sub-honeycomb structure

2. Claim : 9

A serial arrangement of honeycomb structures. The partitioning walls of a downstream honeycomb structure are disposed so as to face at least some of the cells in an upstream honeycomb structure. The flow resistance of fluid in a fluid passage formed by a cell in an upstream honeycomb structure varies from a next passage formed by the adjacent cell, through all cells of the upstream honeycomb structure.

3. Claims: 10-12

A serial arrangement of honeycomb structures. The partitioning walls of a downstream honeycomb structure are disposed so as to face at least some of the cells in an upstream honeycomb structure. The density of cells of an upstream honeycomb structure is higher than the density of cells of a downstream honeycomb structure.

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 00 2759

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-03-2004

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0153157	A	28-08-1985	JP	60131620 U	03-09-1985
			EP	0153157 A2	28-08-1985

DE 4203128	A	13-08-1992	JP	2855860 B2	10-02-1999
			JP	4255513 A	10-09-1992
			DE	4203128 A1	13-08-1992

US 4464185	A	07-08-1984	JP	57147415 A	11-09-1982
			JP	1027767 B	30-05-1989
			JP	58070814 A	27-04-1983

US 6013599	A	11-01-2000	AU	5000099 A	07-02-2000
			CA	2340624 A1	27-01-2000
			EP	1096990 A1	09-05-2001
			JP	2002520149 T	09-07-2002
			WO	0003790 A1	27-01-2000
			US	6248689 B1	19-06-2001

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

